

CSMA 50 to 54 MHz Frequency Utilization Plan

50.000	50.100	CW & Beacons
50.060	50.080	Automatic Control Beacons
50.100	50.600	SSB & CW
50.125		SSB Calling Frequency
50.200		SSB National Calling Frequency
50.400		AM Calling Frequency
50.600	50.800	Non Voice (Digital Packet)
50.800	51.000	Radio Remote Control 20 KHz channels
51.100	51.100	Pacific DX Window
51.120	51.460	Repeater Inputs (500 KHz Split)
51.620	51.960	Repeater Outputs (500 KHz Split)
52.010	52.990	Repeater Inputs (1 MHz Split)
52.525		FM Calling Frequency
53.010	53.990	Repeater Outputs (1 MHz Split)

Repeater Pairs

18 Repeater Pairs 20 KHz Spacing

Output	Input
51.620	51.120
51.640	51.140
51.660	51.160
51.680	51.180
51.700	51.200
51.720	51.220
51.740	51.240
51.760	51.260
51.780	51.280
51.800	51.300
51.820	51.320
51.840	51.340
51.860	51.360
51.880	51.380
51.900	51.400
51.920	51.420
51.940	51.440
51.960	51.460

Repeater Pairs

50 Repeater Pairs 20 KHz Spacing

53.010	52.010
53.030	52.030

53.050	52.050
53.070	52.070
53.090	52.090
53.110	52.110
53.130	52.130
53.150	52.150
53.170	52.170
53.190	52.190
53.210	52.210
53.230	52.230
53.250	52.250
53.270	52.270
53.290	52.290
53.310	52.310
53.330	52.330
53.350	52.350
53.370	52.370
53.390	52.390
53.410	52.410
53.430	52.430
53.450	52.450
53.470	52.470
53.490	52.490
53.510	52.510
53.530	52.530
53.550	52.550
53.570*	52.570*
53.590	52.590
53.610	52.610
53.630	52.630
53.650	52.650
53.670	52.670
53.690	52.690
53.710	52.710
53.730	52.730
53.750	52.750
53.770	52.770
53.790	52.790
53.810	52.810
53.830	52.830
53.850	52.850
53.870	52.870
53.890	52.890
53.910	52.910
53.930	52.930
53.950	52.950
53.970	52.970
53.990	52.990

*** SNP Frequency Pair**